

DRAVO'S NEW RANGE OF HIGH EFFICIENCY UNIT HEATERS

Outputs range from 5 kW to 97 kW.

Sealed combustion circuit.

NOX AISI 441 stainless steel combustion chamber, INOX AISI 441 stainless steel exchanger tubes and fume collection box made of low carbon content.

Efficiency up to 108% referred to the lower heating value (Hi).

Premixed gas modulating burner, low NOx emissions (less than 30 ppm) class 5, in compliance with EN 1020 2009 standards.

Electronic card with continuous modulation of power, controlled by a microprocessor, which allows energy savings of up to 50%.

Very high reduction of air stratification.

An advanced technique of air/gas mixing guarantees total heater safety.

Safety thermostat and condensate control sensor.

230V/1ph/50Hz supply voltage.

In compliance with all applicable EC regulations (0476CQ0451 approval).

Dravo



CONDENSAIRE LK SERIES CONDENSING HEATER

6 models with a output range from 5 – 97kW.

Up to 108% net thermal efficiency.

Modulation down to 20% of full load.

Up to 50% energy saving.

Registered on the Energy Technology List ETL for claiming Enhanced Capital Allowance ECA.

High efficiency means that the modules are BREEAM points qualifying.

Available in natural gas (G20) or LPG (G31).

MODULAIRE LP SERIES MODULATING HEATER

7 models with a output range from 12 – 92kW.

Up to 94% net thermal efficiency.

Modulating burner.

Up to 30% energy saving.

High efficiency means that the modules are BREEAM points qualifying.

Available in natural gas (G20) or LPG (G31).

Microprocessor based controls give continuous modulation.

REGULAIRE LR SERIES ON-OFF & HI-LO HEATER

7 models with a output range from 12 – 92kW.

Turn down to 20% of full load (HI-LO)

Up to 94% net thermal efficiency.


High efficiency means that the modules are BREEAM points qualifying.

Available in natural gas (G20) or LPG (G31).

Rhosili Road, Northampton, NN4 7LZ

Tel: 01604 707022

www.dravo.co.uk • sales@dravo.co.uk



constructionline



Authorised User No. 00138

